

CONFIRMATION

No. 30464501aE/FH/09.06.21

In accordance with the VDI Guideline 2200 (edition June 2007) the gasket type

**DIMERFLEX ST40
DN40/PN40**

of the gasket manufacturer

**DIMER, spol. s r.o
Zelená 505, CZ – 760 01 Zlín-Kudlov**

was verified in a blowout safety test with the following test conditions:

initial gasket stress:	127.7	MPa
temperature of exposure:	300	°C
period of exposure:	48	h
remaining gasket stress:	102.6	MPa

Test step 1

test pressure (absolut):	60	bar
period of leakage measurement:	90	min

Test step 2

reduced gasket stress:	20.9	MPa
test pressure (absolut):	60	bar
period of leakage measurement:	60	min

In both test steps the allowable pressure decay defined in VDI 2200 was not exceeded. Therefore the gasket is in compliance with the requirements of the VDI Guideline 2200 for blowout safety.

This confirmation is only valid in combination with the test report 3046451/a.

Lauffen, June 9th, 2021

amtec Advanced Measurement Messtechnischer Service GmbH



Dipl.-Ing. F. Herkert
Head of Laboratory



Dipl.-Ing. S. Weiler
Test Engineer



Deutsche
Akkreditierungsstelle
D-PL-12008-01-00